

Represented by



(717) 761-7884 sales@envirep.com www.envirep.com

80 SERIES®

Heavy-Duty Self-Priming Centrifugal Pumps



80 SERIES® Heavy-Duty Self-Priming Centrifugal Pumps

Gorman-Rupp 80 Series[®] medium head, mild solids-handling, self-priming centrifugal pumps are designed for non-stop work loads.

The straight-in-suction design of these high efficiency pumps guarantees quick positive priming and allows them to operate at higher suction levels than most other self-priming centrifugal pumps. The liquid being pumped enters directly into the eye of the impeller, and a suction check valve prevents in-line return flow when the pump is shut off.

And, because they have few moving parts, 80 Series pumps are easy to maintain and service, saving money in the long run.

High-Efficiency Impeller

80 Series[®] pumps come equipped with a multi-vane, open impeller for higher efficiencies. Depending on the model, the impeller design will handle up to 2½" solids. These pumps are perfect for mild-solids handling, medium head applications.

Multiple Seal Options

80 Series pumps are standard with mechanical shaft seals. Grease and gland seals are also available depending on the pumping application. Consult factory for details.

Replaceable Wearplate

The replaceable wearplate is vital in ensuring the pump is operating at peak efficiency around the clock and eliminates the need to replace expensive castings. Wearplates are of extra-thick construction allowing for an extended service life.









80 Series[®] self-priming centrifugal pumps are available in a variety of configurations for all of your industrial, construction, mining, agricultural, municipal and petroleum fluidhandling needs.







OTS noted models are included in the Gorman-Rupp OTS pump program. These products are available anytime, anywhere. 01 | Heavy-Duty Pedestal

02 | Ball Bearings

- **03** | Bearing Oil Monitor
- 04 | Mechanical Shaft Seal

Drive Variations



80 Series® Basic pump Size: 1.25" (30 mm) to 6" (150 mm) Max Capacity: 1860 GPM (117.3 lps) Max Head: 205' (62.5 m) Max Solids: 2.5" (63.5 mm) Seal Elastomer: Viton® Material of Construction: Cast Iron*



05 | Balanced Impeller

06 | Replaceable

07 | Volute

Wearplate

08 | Discharge Outlet

80 Series® Close-coupled Shown with explosion-proof motor Size: 1.25" (30 mm) to 1.5" (38 mm) Max Capacity: 92 GPM (5.8 lps) Max Head: 70' (21.3 m)

Seal Elastomer: Viton® Material of Construction: Cast Iron*



80 Series® Engine driven Size: 2" (50 mm) to 6" (150 mm) Max Capacity: 1860 GPM (117.3 lps) Max Head: 210' (64.0 m) Max Solids: 2.5" (63.5 mm) Seal Elastomer: Viton® Material of Construction: Cast Iron, Aluminum


- 09 | Suction Check Valve
- 10 | Suction Inlet

80 Series® Shield-A-Spark portable engine driven Size: 2" (50 mm) to 3" (75 mm) Max Capacity: 395 GPM


(24.9 lps) Max Head: 140' (42.7 m) Seal Elastomer: Viton® Material of Construction: Aluminum Engines: Gasoline, Diesel

*Some models available in additional materials. Consult factory for details.

Pump Performance Data



3" to 6" Models



Viton[®] is a registered trademark of DuPont Performance Elastomers. All rights reserved.

FLUID-HANDLING EQUIPMENT DESIGNED WITH YOUR NEEDS IN MIND



 \star Manufacturing Facilities

• Distribution Centers

Mansfield, Ohio, USA Gorman-Rupp Canada St. Thomas, Ontario, Canada Gorman-Rupp Europe Waardenburg, Netherlands Namur, Belgium

Gorman-Rupp Africa Cape Town, South Africa Durban, South Africa Johannesburg, South Africa (Headquarters) **Distribution Centers** Dubai, United Arab Emirates Grand Prairie, Texas, USA

Engineering and manufacturing superiority has been the hallmark of Gorman-Rupp since our inception in 1933. Today we bring our products to life in some of the most efficient, modern and state-of-the-art manufacturing facilities in the world. Gorman-Rupp has a selection of nearly 3,000 pump models, and our world-class team of distributors has worked closely with thousands of end users around the world. We have the proven expertise and the resources to specify, manufacture, test and service your pump, and to ensure reliable performance for the long haul.



Represented by

(717) 761-7884 sales@envirep.com www.envirep.com GORMAN-RUPP PUMPS P.O. BOX 1217 MANSFIELD, OHIO 44901-1217 | USA TEL: 419.755.1011 | FAX: 419.755.1251

GRPUMPS.COM



the fump feople.

Product information is subject to change; consult factory for details. All images are for illustrative purposes only. Actual product may vary from printed representation. © 2008-2020 The Gorman-Rupp Company. All rights reserved. Printed in the USA

AV-05972_REV092020